





Technical Data

		according to UL	according to VDE
Insulation co-ordination according to DIN/VDE 0110-1 04.97			
pin spacing		0.200 in.	5.08mm / 10.16mm
voltage		300V / 600V	250V-eff / 630V-eff
			according to VDE 0110 degree of contamination 3
Insulation material group			insulating material I: 600 ? CTI
minimum clearances or creepage distances			3.2mm
			at connected solid wire ø2.3mm
maximum current		12A /AWG12	12A /4mm?
tightening torque		4.5 lb-in	0.5 Nm max.
at connected nominal diameter			
wire range		AWG Cu, Sol/Str wire No. 28-12	ø0.3mm - ø2.3mm
		<single-wire>	stranded wire AWG
rated cross section	mm?	4	2.5 12
contact resistance		<5mΩ at I= 500mA after 100 plug contacts per pole from the clamping point via the head per circuit 1.0N .. 3.0N	
withdrawing force			
max. limiting temperature		+125°C	
min. limiting temperature		-40°C	
climatic class		40/125/56 according to DIN IEC 68-1	
type of protection according to IEC 529		IP 20 at connected nominal diameter	
number of poles		2 - 24 poles	
wire strip length		8mm	
approvals		UL CSA SEV	

Materials

item 1	insulating body		
	part-no. 711853-213-02-2		
through	part-no. 711853-213-24-2	PA 66 Frianyl A63 V0 black (unbreakable) flame resistant and self-extinguishing, according toUL 94V-0 stated under the File-No. E86034 (M); temperature range -40°C to +125°C, for a short time up to 185°C	
Item 2	terminal molding cover		
	part-no. 711854-213-02-2		
through	part-no. 711854-213-24-2		
item 3	connector body M3	brass CuZn39 Pb2	
	part-no. 718503-0116	4ám nickel plated	
Item 4	terminal screw M3	steel quality 8.8	
	part-no. 795059-01	4ám nickel plating over 8ám copper plating (standard)	
item 5	wire protector detached	copper alloy CuSn6	
	part-no. 717176-01	0,8-3,3ám tin plated	
(01)	or wire protector on strip		
	part-no. 717176-02		

Verwendungsbereich				Zul.Abw.		Oberfläche	Maßstab 5:1		Gewicht
							Werkstoff, Halbzeug		Werkstoff-Artikelnummer
					Datum	Name	Benennung		
				Bearbv	03.06.98	R+sch	data sheet series type 214 ps 5.08mm		
				Gepr.v					
				Norm					
							Artikelnummer	Teile-Code	Blatt
01	1 x NL 3M 467/99	22.11.99	Stad.			RIA	31214	9-7232	1
Zust.	Änderung	Datum	Name	CAD-Nr.	0100000000006u		Ers.d:	Ers.f.:	v.1 Bl.

Diese unsere vertrauliche Zeichnung darf ohne unsere vorherige schriftliche Zustimmung weder kopiert noch gedruckt werden, und sie darf auch nicht in anderer Weise mißbräuchlich verwendet werden.

T
NW
QS
TPSB
TPK
TPR
TAVR
NAVA
NAVA-E ☒
NWLR
TPB
TAVB
NAVR
NWLB
TWSF
TWST
NAVT
G?tepr.
KonForm
NAMS ☒