



Specifications

Description AJP30A

Unshielded
10 positions

Technical Data AJP30A

Electrical: UL applications: 250 volts AC max at 2 amps

Dielectric withstanding voltage: 500 volts AC

Insulation resistance: 500 megohms

Termination: resistance 35 milliohms max after environmental testing

Mechanical: Cable-to-plug tensile strength: 20lbs min

Durability: 2000 mating cycles

Material & Finish: Housing: polycarbonate, UL94V-2

Color: clear

Contact blade: phosphor bronze

Conductor: stranded & solid wire 24, 26 AWG

Plating: 30u" gold

Ordering Information

| | | | | | | |
|--------|-----------|----------|-----------|----------|---|---|
| AJP30A | 8 | 8 | 2 | 3 - X | 2 | 1 |
| Type | Positions | Contacts | Wire Type | Plating | | |
| | | | Round | 3 = 30u" | | |
| | | | | 4 = 50u" | | |

X=1(Stranded Wire) or 3(Stranded & Solid Wire)
2=94V2 Plastic Type
1=Long Body

| | |
|--------------------------------|------------------------------|
| RIA CONNECT | P/N: AJP30A8823-X21 |
| Desc.: Unshielded plug, CAT 5e | |
| Date: 9-23-08 | Drawn By: Donna Mears |
| Dimensions in mm | Verified By: Mike Balekdjian |