



PCB LAYOUT
Ref.

MATERIAL:

- HOUSING—DSM STANYL TE250F6 (NYLON-46)
HEAT DEFLECTION TEMP.290°
BLACK COLOR, UL94V-0
- CONTACTS—0.35mm THICK PHOS-BRONZE PLATED
WITH HARD GOLD AND GOLD FLASH IN
SOLDER AREA.

CAVITY CONFIRMS TO FCC RULES AND REGULATIONS
PART 68,SUBPART F.

Ordering Information

AJT32L 8 8 X X-0 X 0

Type Positions Contacts Ports Plating
2, 4 1=6u"
5, 6 3=30u"

| | LED1 | LED2 | | LED1 | LED2 |
|----|--------|--------|----|---------|---------|
| 1= | Yellow | Green | 5= | Green | Red |
| 2= | Green | Green | 6= | Red | Green |
| 3= | Green | Yellow | 7= | Yellow | Yellow |
| 4= | Green | Orange | 8= | Grn/Ylw | Grn/Ylw |

Tolerance
unless otherwise specified

.0 ± .25
.00 ± .20
.000 ± .10

| | |
|--|---|
| | P/N: AJT32L88XX-0X0 |
| | Desc.: Top entry, unshielded, LED, thru hole modular jack |
| Date: 7-16-09 | |
| Dimensions in mm Drawn By: Donna Mears | |